

I. Making the stage frame

- A. Building the stage frame:
 - 1. The top, from elbow to elbow is glued into one piece
 - 2. The bottom, from elbow to elbow is glued into one piece
 - 3. The uprights are glued into one piece each with a short piece of pipe glued into each end to plug into the elbows when the stage is assembled.
- B. Be careful not to allow glue to get into the fittings where the pieces with plug-in and be removed when the stage is assembled and dis-assembled.

II. Assembling the stage :

- A. Install the bottom small rod between front upright and rear upright
- B. Slide side curtain onto the top side curtain rod and install between the front upright and the rear upright.
- C. Stand uprights into the bottom piece and then install the top piece to complete the assembly of one side.
- D. Repeat this assembly for the other side.
- E. Install the front bottom bar between the two end pieces.
- F. Install the rear bottom bar between the two end pieces.
- G. Slide the front curtain onto the front curtain bar and install between the two end pieces.
- H. Slide the top curtain onto the top curtain rod and install between the two end pieces.
- I. Slide the two back curtains onto the bar curtain bar and install between the to end pieces.

III. Stage Modifications:

- A. Our stage has an additional upper curtain. This is created by adding a T , 12” behind the top curtain, with the open part of the T pointing up. Cut two pieces of 1 1/4” pipe 12” long and glue an EL onto one end of each. These are installed into the Ts and joined by a 6’ piece of pipe to create another top rod, 12” higher and 12” behind the original top curtain.
- B. An additional curtain must be made of the heavier material, the same with of the top curtain and 14” tall.